

### Main Features

- Multiple functions including torque setting, unit setting, mode setting, data storage, data clear, data output and online calibration.
- 9 pre-settable target torque values.
- Functions in both clockwise and anticlockwise directions.
- LCD display showing N-m, ft-lb, in-lb and kg-cm measurements.
- Audible and visible torque confirmation by means of buzzer and 12 LED display.
- Data memory size 50 or 250 optional.
- 250 data memory points with PC connectivity for data download (software included) ★



Model No.	WE2-030BN	WE3-135BN	WE4-200BN	WE4-340BN	WE6-500BN	WE6-850BN
	WK2-030BR	WK3-135BR	WK4-200BR	WK4-340BR		
Measured Torque Range	1,5-30Nm 1,11-22,12 ft-lb 13,3-265,5 in-lb 15,3-306 kg-cm	6,8-135 Nm 5-99,5 ft-lb 60-1195 in-lb 69-1378 kg-cm	10-200 Nm 17,4-147,5 ft-lb 88-1770 in-lb 102-2041 kg-cm	17-340 Nm 12,5-250,7 ft-lb 150-3009 in-lb 173-3469 kg-cm	25-500Nm 8,4-368,7 ft-lb 221-4424 in-lb 255-5102 kg-cm	42,5-850 Nm 31,3-626,8 ft-lb 376-7521 in-lb 434-8674 kg-cm
Resolution	0,01Nm 0,01 ft-lb 0,1 in-lb 0,1 kg-cm	0,1Nm 0,1 ft-lb 1 in-lb 1 kg-cm	0,1Nm 0,1 ft-lb 1 in-lb 1 kg-cm	0,1Nm 0,1 ft-lb 1 in-lb 1 kg-cm	0,1Nm 0,1 ft-lb 1 in-lb 1 kg-cm	0,1Nm 0,1 ft-lb 1 in-lb 1 kg-cm
Sq. Dev. (in)	1/4	3/8	1/2	1/2	3/4	3/4
Length (mm)	390	415	530	650	950	1220
Accuracy	CW : ±2%; CCW : ±3%					
Pre-Setting No.	WE : 1 Set; WK : 9 Sets					
Head Type	Lever Type Ratchet					
Bright LED	WE Series - 12 LD (4 Red + 8 Green) WK Series - 12 LD (2 Red + 10 Green)					
Battery	AA X 2					
Battery Life	110 hrs (continuous) ; 1 year (standby)					
Unit Selection	Nm, in-lb, ft-lb, kg-cm					
Operation Mode	Peak hold / Track					
Operation Temp.	-10°C - 60°C					
Drop Test	1m					
Vibration Test	10G					

★ Features available only in WK Series

★★ WK Series is with PC Connectivity and 250 Data Memory Size.