

Q-TORQ™

PC Model Preset Torque Wrench

- Easy to adjust to desired torque - appropriate torque tester required.
 - Double Lock System - Operator cannot change set torque without appropriate tool.
 - ±4% Accuracy in clockwise direction from 20% to 100% Max. Torque.
 - Various kinds of heads designed for different applications.
 - Extensively used in production lines.
- **PC Model:** Single piece construction with ratchet head for clockwise and counter-clockwise operation.
 - **PH / PCH Model:** 2 piece construction head holder for standard 9 x 12, 14 x 18, 24 x 32, 27 x 36 mm square shank heads.



Torque Adjusting Tool



(Metric)

Item No.	Square Drive	Torque Range		Length mm	Width mm	Weight Kg
		N.m	Lb.ft			
PC112	1/4"	2.5-12	20-205*	184	30	0.45
PC120	1/4"	4-20	30-180*	184	30	0.45
PC230	3/8"	6-30	50-250*	214	37	0.5
PC260	3/8"	10-60	9.0-45	255	38	0.56
PC2125	3/8"	25-125	20-90	366	38	0.79
PC3200	1/2"	40-200	30-150	457	40	1.2
PC3340	1/2"	65-340	50-250	691	40	1.96
PC4500	3/4"	100-500	80-400	915	57	2.8
PC4650	3/4"	150-650	100-500	915	57	2.8
PC4800	3/4"	160-800	120-600	1030	60	5
PC41000	3/4"	200-1000	150-750	1260	60	6
PC51000	1"	200-1000	150-750	1260	60	6

*Unit is Lb.in

Note: Technical parameters subject to change.

(Metric)

Item No.	Square Drive	Torque Range		Length mm	Width mm	Weight Kg
		N.m	Lb.ft			
PCH920	9x12	4-20	30-180*	155	20	0.24
PH925T1	9x12	5-25	45-225*	178	28	0.28
PCH940	9x12	8-40	3.7-37	178	20	0.30
PH950T1	9x12	5-50	4.0-40	240	28	0.4
PH985T1	9x12	15-85	12-60	310	28	0.51
PH9120T1	9x12	25-120	20-90	355	28	0.6
PH14200T1	14x18	40-200	30-150	424	32	0.86
PH14300T1	14x18	50-300	40-225	688	32	1.3
PH14500T1	14x18	100-500	80-400	970	56	2.56
PH24650T1	24x32	150-650	100-500	1030	56	4.9
PH24800T1	24x32	160-800	120-600	1030	56	4.9
PH241000T1	24x32	200-1000	150-750	1260	56	5.7
PH271500T1	27x36	300-1500	400-1100	1610	64	8