

HOLEX® Torque wrench with dial gauge display



Version: One-armed; slim design with easily readable dial gauge. Body entirely of steel, chrome-plated with fixed square drive for plug-in heads.

Size 6 – 280 – Non-slip 2-component handle.

Size 420 – 1000 – Knurled metal handle.

Function: Actual torque can be read on the gauge whilst working; the final value is held by the memory pointer to be read later.

Application: For controlled single tightening of screws and for controlled measurements.



65 5520_6 – 280

65 5520_420 – 1000

| Size = Maximum torque | | Nm | 6 | 12 | 25 | 50 | 100 | 200 | 280 | 420 | 700 | 1000 |
|-----------------------|--------------------|---------------------------------------|-------------|--------|--------|--------|----------|----------|----------|----------|----------|------------|
| new | 6ZE 65 5520 | Torque wrench with dial gauge display | XXX | XXX | XXX | XXX | XXX | XXX | XXX | XXX | XXX | XXX |
| | | Tightening value (scale range) | Nm 1 – 6 | 2 – 12 | 5 – 25 | 5 – 50 | 10 – 100 | 20 – 200 | 30 – 280 | 50 – 420 | 70 – 700 | 100 – 1000 |
| | | Scale graduation, 1 graduation = | Nm 0.1 | 0.2 | 0.5 | 0.5 | 1 | 2 | 5 | 5 | 10 | 10 |
| | | Overall length | mm 225 | 225 | 250 | 332 | 380 | 470 | 690 | 890 | 1258 | 1490 |
| | | Weight | kg 0.4 | 0.4 | 0.4 | 0.6 | 0.7 | 1 | 1.65 | 2.5 | 5.5 | 6.4 |
| | | Square drive | inches 1/4" | 1/4" | 1/4" | 3/8" | 1/2" | 1/2" | 1/2" | 3/4" | 3/4" | 1" |